



GYROSCOPIC MIXER **ROTA X.40**

»The **Ergonomic & Multitalented Mixer**«

Outstanding working ergonomics!
Patented splash proof design.

- | Dispersions
- | Facade paints
- | Plasters
- | Wood protection

PRODUCT
VIDEO



smartCONNECT
READY

Reliable

Virtually no downtime caused by dirty drive and clamping elements thanks to the unique & patented protection mechanism. We call it »Splash Guard«.

Ergonomic

Outstanding ergonomics as minimal effort is required for loading and unloading. Machine loading that doesn't put strain on the back due to easy Push & Slide.

Quick

No rubber band needed to fix the handle! Save time with the automatic handle fixation and integral door with an Auto-Open-Function. The mixer is waiting for you - not you for the mixer!

MADE IN

GERMANY

 **Collomix**
.colorTEC

ROTA X.40

Low throughput

Medium throughput

High throughput

Very high throughput

Features

- Simple and space-saving handling due to automatically opening integral door.
- Complete »auto-mixing function«: Start by pushing the auto-button or start machine automatically by simply closing the door.
- Accelerometer for detecting vibrations. Automatic parameter adjustment possible.
- High mixing efficiency with very short mixing times.
- Smooth-running with large and heavy containers.
- Low noise emission at the POS due to maintenance-free toothed belt drive.
- Particularly kind to containers due to biaxial mixing of even viscous materials.
- Integration in PoS solutions; can also be combined with roller conveyors.
- smartCONNECT option for remote data tracking and service.

GYROSCOPIC
MIXER

ROTA
X.40

Technical data

CONTAINER	
Max. mixing weight	40 kg
Rec. continuous working weight	30 kg
Clamping height	60 - 400 mm
Max. container diameter	round: 350 mm / oval: 360 x 330 mm
Container type	round / oval / metal / plastic
Multiple containers at the same time	yes (only with centring ring)
PERFORMANCE	
Power supply	230 V / 50 Hz (110 V / 60 Hz optional)
Motor output	1.1 kW
Max. speed	145 rpm (programmable)
Rec. mixing throughput	medium
OPERATION	
Mixing times	3 programmable times
Clamping pressure	automatic - depending on 3 selectable container heights
Door option	automatic integral door
Loading type	Push & Slide incl. loading board
Clamping plate / loading height	455 mm (+ 15 mm)
Can be combined with roller conveyor	yes
SHIPPING AND INSTALLATION	
Machine dimensions (W x D x H)	796 x 986 x 1174 mm
Machine weight	176 kg
Shipping dimensions (W x D x H)	1000 x 800 x 1350 mm
Shipping weight	190 kg
Transport rollers	yes
Installation	adjustable 4-foot installation
SERVICE	
Splash guard index	patented complete splash protection



Collomix GmbH

Daimlerstraße 9
85080 Gaimersheim
Germany

P: +49 (0) 8458 / 32 98 0

F: +49 (0) 8458 / 32 98 30

E: info@collomix.de

www.collomix.com